

CLAIMS

1. A light emitting element comprising a plurality of layers interposed between a pair of electrodes opposed to each other,

5 wherein at least one of the plurality of layers is formed of a layer containing a light emitting material, and

 wherein the layer containing the light emitting material is interposed between a layer containing an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property, and a layer containing
10 an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property.

2. A display device comprises the light emitting element according to claim 1 in a pixel portion.

15

3. A light emitting element comprising a plurality of layers interposed between a pair of electrodes opposed to each other,

 wherein at least one of the plurality of layers is formed of a layer containing a light emitting material, and

20 wherein the layer containing the light emitting material is interposed between a layer containing an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property, and a layer containing an oxide semiconductor or metal oxide, a material having a higher electron transporting property than a hole transporting property and a material which can donate an electron
25 to the material having a higher electron transporting property than a hole transporting property.

4. A display device comprises the light emitting element according to claim 3 in a pixel portion.

30

5. A light emitting element comprising:
a pair of electrodes; and
first to third layers sequentially laminated between the pair of electrodes,
wherein the first layer contains an oxide semiconductor or metal oxide and a
5 material having a higher hole transporting property than an electron transporting
property,
wherein the second layer contains a light emitting material, and
wherein the third layer contains an oxide semiconductor or metal oxide and a
material having a higher electron transporting property than a hole transporting
10 property.

6. A light emitting element according to claim 5, wherein the first layer
comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

15 7. A display device comprises the light emitting element according to claim 5
in a pixel portion.

8. A light emitting element comprising:
a pair of electrodes; and
20 first to third layers sequentially laminated between the pair of electrodes,
wherein the first layer contains an oxide semiconductor or metal oxide and a
material having a higher hole transporting property than an electron transporting
property,
wherein the second layer contains a light emitting material, and
25 wherein the third layer contains an oxide semiconductor or metal oxide, a
material having a higher electron transporting property than a hole transporting property,
and a material which can donate an electron to the material having a higher electron
transporting property than a hole transporting property.

30 9. A light emitting element according to claim 8, wherein the first layer

comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

10. A display device comprises the light emitting element according to claim 8 in a pixel portion.

5

11. A light emitting element comprising:

a pair of electrodes; and

first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

wherein the third layer contains an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property,

15 and

wherein the fourth layer contains an oxide semiconductor or metal oxide, a material having a higher electron transporting property than a hole transporting property, and a material which can donate an electron to the material having a higher electron transporting property than a hole transporting property.

20

12. A light emitting element according to claim 11, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

13. A display device comprises the light emitting element according to claim 11 in a pixel portion.

25

14. A light emitting element comprising:

a pair of electrodes; and

first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a

30

material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

wherein the third layer contains an oxide semiconductor or metal oxide and a
5 material having a higher electron transporting property than a hole transporting property,
and

wherein the fourth layer contains a material having a higher electron
transporting property than a hole transporting property and a material which can donate
an electron to the material having a higher electron transporting property than a hole
10 transporting property.

15. A light emitting element according to claim 14, wherein the first layer
comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

15 16. A display device comprises the light emitting element according to claim 14
in a pixel portion.

17. A light emitting element comprising:

a pair of electrodes; and

20 first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a
material having a higher hole transporting property than an electron transporting
property,

wherein the second layer contains a light emitting material,

25 wherein the third layer contains an oxide semiconductor or metal oxide and a
material having a higher electron transporting property than a hole transporting property,
and

wherein the fourth layer contains an oxide semiconductor or metal oxide and a
material having a higher hole transporting property than an electron transporting
30 property.

18. A light emitting element according to Claim 17, wherein the first layer and the fourth layer are formed using the same material.

5 19. A light emitting element according to claim 17, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

20. A display device comprises the light emitting element according to claim 17 in a pixel portion.

10

21. A light emitting element comprising:

a pair of electrodes; and

first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a
15 material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

wherein the third layer contains an oxide semiconductor or metal oxide, a
material having a higher electron transporting property than a hole transporting property,
20 and a material which can donate an electron to the material having a higher electron transporting property than a hole transporting property, and

wherein the fourth layer contains an oxide semiconductor or metal oxide, a
material having a higher electron transporting property than a hole transporting
property.

25

22. A light emitting element according to Claim 21, wherein the first layer and the fourth layer are formed using the same material.

23. A light emitting element according to claim 21, wherein the first layer
30 comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

24. A display device comprises the light emitting element according to claim 21 in a pixel portion.

5 25. A light emitting element comprising:
a pair of electrodes; and
first to fifth layers sequentially laminated between the pair of electrodes,
wherein the first layer contains an oxide semiconductor or metal oxide and a
material having a higher hole transporting property than an electron transporting
10 property,
wherein the second layer contains a light emitting material,
wherein the third layer contains an oxide semiconductor or metal oxide and a
material having a higher electron transporting property than a hole transporting
property,
15 wherein the fourth layer contains an oxide semiconductor or metal oxide, a
material having a higher electron transporting property than a hole transporting property,
and a material which can donate an electron to the material having a higher electron
transporting property than a hole transporting property, and
wherein the fifth layer contains an oxide semiconductor or metal oxide and a
20 material having a higher hole transporting property than an electron transporting
property.

26. A light emitting element according to Claim 25, wherein the first layer and
the fifth layer are formed using the same material.

25

27. A light emitting element according to claim 25, wherein the first layer
comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

28. A display device comprises the light emitting element according to claim 25
30 in a pixel portion.

29. A light emitting element comprising:
a pair of electrodes; and
first to fifth layers sequentially laminated between the pair of electrodes,
5 wherein the first layer contains an oxide semiconductor or metal oxide and a
material having a higher hole transporting property than an electron transporting
property,
wherein the second layer contains a light emitting material,
wherein the third layer contains an oxide semiconductor or metal oxide and a
10 material having a higher electron transporting property than a hole transporting
property,
wherein the fourth layer contains a material having a higher electron
transporting property than a hole transporting property and a material which can donate
an electron to the material having a higher electron transporting property than a hole
15 transporting property, and
wherein the fifth layer contains an oxide semiconductor or metal oxide and a
material having a higher hole transporting property than an electron transporting
property.
- 20 30. A light emitting element according to Claim 29, wherein the first layer and
the fifth layer are formed using the same material.
31. A light emitting element according to claim 29, wherein the first layer
comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.
25
32. A display device comprises the light emitting element according to claim 29
in a pixel portion.